

Job Name:	Location:
Purchaser:	
Engineer:	
Submitted To:	For: <input type="checkbox"/> Reference <input type="checkbox"/> Approval <input type="checkbox"/> Construction
Submitted By:	Date:
Unit Designation: Schedule #:	Model No.:

For use with the following Daikin VRV Models: FXAQ; FXFQ; FXHQ; FXLQ; FXMQ; FXNQ; FXSQ; FXDQ; FXOQ
 For use with the following Daikin SkyAir Models: FCQ, FHQ

FEATURES / BENEFITS
<ul style="list-style-type: none"> For a maximum of 16 groups of indoor units (max. 128 units), unified operation/stop or individual operation/stop can be performed with this optional accessory. Also allows you to check operation/error display at a glance. By combining with a central remote controller and schedule timer, you can construct a system that matches the size and use of the building. Up to 8 units connectable within 1 system. Up to 16 units in the double central control mode. Applicable wiring methods include bus and star in addition to crossover type. Can be used in combination with other D-BACS equipment.



OPERATION	Start/Stop
	Permit/Prohibit Selection
MONITORING	Status
	Malfunction Flashing
CONTROL M'GMNT	Group Setting

SPECIFICATIONS OF CORD	
TYPE	2-core sheathed vinyl cord or cable
SIZE	AWG 18-2
TOTAL LENGTH	6560 ft

POWER SUPPLY	
POWER SUPPLY	208-230-/1/60

