

YANMAR

ENCP850JJ 24 RT/84 kW



The YANMAR Variable Refrigerant Flow (VRF) natural gas heat pump system provides a flexible way to efficiently heat and cool many different types of buildings. By using natural gas to power a YANMAR gas engine, YANMAR's VRF system is able to reduce electrical costs by 90% and lower average operating costs by 30% over a standard electric system.

Model			ENCP850JJ
Capacity	Cooling	Nominal Tons	24
		KW	84
	Heating	BTU	324,200
		kW	95
	Low Temp/	BTU	279,700
	Cold Temp Heating	kW	82
Outdoor Unit	Number of Pipes	#	2
Indoor Unit (IDU) Connections	IDU Total Capacity	%Min - %Max	50-130
	Max Number of Connectable IDU	#	48
Electrical	Power Supply Voltage (Frequency)	V (HZ)	240 (60) Single Phase
	Operating Current for Cooling/Heating	A/A	7.93/7.21
	Power Consumption for Cooling/Heating	kW/kW	1.66/1.51
Fuel Consumption HHV	Natural Gas for Cooling	BTU/Hr. (kW)	205,590 (60.2)
	Natural Gas for Heating	BTU/Hr. (kW)	201,318 (58.9)
Sound Level	Normal/Quiet Mode	dB(A)	62/59
Fans	Number of Units	#	3
Pipe Size Data	Refrigerant Suction Line	in. (mm.)	1.07 (27.21)
	Refrigerant Liquid Line	in. (mm.)	.75 (19.05)
	Natural Gas Fuel Pipe Thread & Size	NPT	3/4
Dimensions	Height	in. (mm.)	85.44 (2,170.11)
	Width	in. (mm.)	82.67 (2,099.87)
	Depth	in. (mm.)	31.50 (800.10)
	Weight	lb. (kg.)	2,380 (1,079.55)
Refrigerant	Туре	-	R410(A)
	Charge	lb. (kg.)	26 (11.8)
Operating Range	Cooling	°F (°C)	14 to 116 (-10 to 46)
	Heating	°F (°C)	-4 to 96 (-20 to 35)
Standard Limited Warranty	Condensing Unit*	Years/Hours	5/20,000 Parts** 1/4,000 Labor 7/28,000 Compressor
	Fan Coil Unit and Indoor Accessories	-	1 Year Parts
Emissions & Certifications			Not for sale in U.S.

^{*} Provided that all scheduled maintenance is completed according to the VRF Condensing Unit's limited warranty statement. Offerings based on year or hours, whichever comes first.

^{**} Excludes compressor