

Submittal Data Sheet

0.6-Ton Round Flow Sensing Cassette FXFQ07TVJU

PERFORMANCE			
Indoor Unit Model No.	FXFQ07TVJU	Indoor Unit Name:	0.6-Ton Round Flow Sensing Cassette
Type:	Cassette	Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75
Rated Cooling Capacity (Btu/hr):	7,200	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43
Sensible Capacity (Btu/hr):	6,700	Rated Piping Length(ft):	
Cooling Input Power (kW):	0.030	Rated Height Separation (ft):	
Rated Heating Capacity (Btu/hr):	8,500		
Heating Input Power (kW):	0.02		

INDOOR UNIT DETAILS			
Power Supply (V/Hz/Ph):	208-230 / 60 / 1	Airflow Rate (HH/H/L) (CFM):	420/406/353
Power Supply Connections:	L1, L2, Ground	Moisture Removal (Gal/hr):	
Min. Circuit Amps MCA (A):	0.3	Gas Pipe Connection (inch):	1/2
Max Overcurrent Protection (MOP) (A):	15	Liquid Pipe Connection (inch):	1/4
Dimensions (HxWxD) (in):	9-11/16 x 33-1/16 x 33-1/16	Condensate Connection (inch):	1-1/4
Net Weight (lb):	42	Sound Pressure (H/L) (dBA):	29/27
Ext. Static Pressure (Rated/Max) (inWg):	I	Sound Power Level (dBA):	

Daikin North America LLC, 5151 San Felipe, Suite 500, Houston, TX, 77056


Submittal Date: 9/12/2018 8:54:10 AM Page 2 of 3





Submittal Data Sheet


0.6-Ton Round Flow Sensing Cassette FXFQ07TVJU


DIMENSIONAL DRAWING











Unit : in. (mm

ITEM	PART NAME	REMARK
1	Liquid pipe connection	ϕ 3/8 (ϕ 9.5) Flare connection
2	Gas pipe connection	ϕ 5/8 (ϕ 15.9) Flare connection
3	Drain pipe connection	VP25 (0. D. φ1-1/4 (φ32), I. D. φ1 (φ25))
4	Power supply entry hole	
5	Transmission wiring entry hole	
6	Air Outlet	
7	Air Inlet grille	
8	Corner decoration cover	
9	Sensor	Infrared presence sensor Infrared floor sensor
10	Knock out hole	φ3-15/16 (φ100)

Vithout panel	H1	10 (256)
	W1	33-1/16 (840)
	D1	33-1/16 (840)
With panel	H2	11-11/16 (296)
	W2	37-3/8 (950)
	D2	37-3/8 (950)

Notes) 1. Location of the nameplates

- Unit body: on the control box cover.
 Decoration panel: on the panel frame at the motor side
- 2. Make sure the spacing between the ceiling and the cassette is no more than 1-3/8"(35mm).
- When the conditions exceed 86°F(30°C) and RH 80% in the ceiling or fresh air is inducted into the ceiling an additional insulation is required (polyethylene foam, thickness 3/8"(10mm) or more).

Note: For additional dimensional data and clearance information, refer to Engineering Data

Daikin North America LLC, 5151 San Felipe, Suite 500, Houston, TX, 77056

www.daikinac.com www.daikincomfort.com

Daikin City Generated Submittal Data

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

Submittal Date: 9/12/2018 8:54:10 AM Page 3 of 3