



## Submittal Data Sheet

1.0-Ton Concealed Floor Standing

FXNQ12MVJU9

### PERFORMANCE

Indoor Unit Model No.	FXNQ12MVJU9	Indoor Unit Name:	1.0-Ton Concealed Floor Standing
Type:	Floor Standing	Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75
Rated Cooling Capacity (Btu/hr):	12,000	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43
Sensible Capacity (Btu/hr):	8,300	Rated Piping Length(ft):	
Cooling Input Power (kW):	0.080	Rated Height Separation (ft):	
Rated Heating Capacity (Btu/hr):	13,500		
Heating Input Power (kW):	0.08		

### INDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	208-230 / 60 / 1	Airflow Rate (H/L) (CFM):	280/210
Power Supply Connections:	L1, L2, Ground	Moisture Removal (Gal/hr):	
Min. Circuit Amps MCA (A):	0.5	Gas Pipe Connection (inch):	1/2
Max Overcurrent Protection (MOP) (A):	15	Liquid Pipe Connection (inch):	1/4
Dimensions (HxWxD) (in):	24 x 42-1/8 x 8-5/8	Condensate Connection (inch):	25/32
Net Weight (lb):	56	Sound Pressure (H/L) (dBA):	36/33
Ext. Static Pressure (Rated/Max) (inWg):	/	Sound Power Level (dBA):	

**Submittal Data Sheet**  
 1.0-Ton Concealed Floor Standing  
 FXNQ12MVJU9

**DIMENSIONAL DRAWING**

