



## Submittal Data Sheet

2.5-Ton Multi Position Air Handling Unit

FXTQ30TAVJUA

### PERFORMANCE

Indoor Unit Model No.	FXTQ30TAVJUA	Indoor Unit Name:	2.5-Ton Multi Position Air Handling Unit
Type:	Ducted	Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75
Rated Cooling Capacity (Btu/hr):	30,000	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43
Sensible Capacity (Btu/hr):	21,400	Rated Piping Length(ft):	
Cooling Input Power (kW):	0.410	Rated Height Separation (ft):	
Rated Heating Capacity (Btu/hr):	34,000		
Heating Input Power (kW):	0.41		


### INDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	208/230 / 60 / 1	Airflow Rate (H/M/L) (CFM):	1000/850/700
Power Supply Connections:		Moisture Removal (Gal/hr):	
Min. Circuit Amps MCA (A):	4.9/4.9	Gas Pipe Connection (inch):	5/8
Max Overcurrent Protection (MOP) (A):	15	Liquid Pipe Connection (inch):	3/8
Dimensions (HxWxD) (in):	45 x 17.5 x 21	Condensate Connection (inch):	3/4
Net Weight (lb):	115	Sound Pressure ( ) (dBA):	
Ext. Static Pressure (Rated/Max) (inWg):	/ 0.9"	Sound Power Level (dBA):	



**Submittal Data Sheet**  
2.5-Ton Multi Position Air Handling Unit  
FXTQ30TAVJUA

**DIMENSIONAL DRAWING**



FXTQ09/12/18/24/30/36 TAVJU