

Submittal Data Sheet

4.0-Ton Multi Position Air Handling Unit FXTQ48TAVJUA

PERFORMANCE			
Indoor Unit Model No.	FXTQ48TAVJUA	Indoor Unit Name:	4.0-Ton Multi Position Air Handling Unit
Туре:	Ducted	Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75
Rated Cooling Capacity (Btu/hr):	48,000	Rated Heating Conditions:	Indoor (°F DB/WB): / 70 Ambient (°F DB/WB): 47 / 43
Sensible Capacity (Btu/hr):	32,700	Rated Piping Length(ft):	
Cooling Input Power (kW):	0.520	Rated Height Separation (ft):	
Rated Heating Capacity (Btu/hr):	54,000		
Heating Input Power (kW):	0.52		

INDOOR UNIT DETAILS			
Power Supply (V/Hz/Ph):	208-230 / 60 / 1	Airflow Rate (H/M/L) (CFM):	1,520/1,290/1,060
Power Supply Connections:		Moisture Removal (Gal/hr):	
Min. Circuit Amps MCA (A):	6.50	Gas Pipe Connection (inch):	5/8
Max Overcurrent Protection (MOP) (A):	15.00	Liquid Pipe Connection (inch):	3/8
Dimensions (HxWxD) (in):	53.43 x 21 x 21	Condensate Connection (inch):	3/4
Panel (HxWxD) (in):		Sound Pressure (H) (dBA):	54
Net Weight (lb):	150	Sound Power Level (dBA):	62
Panel Weight (lb):		Ext. Static Pressure (Rated/Max) (inWg):	0.90 / 0.90



Submittal Data Sheet

4.0-Ton Multi Position Air Handling Unit FXTQ48TAVJUA

DIMENSIONAL DRAWING

